

**6EW6****SHARP-CUTOFF PENTODE**

7-PIN MINIATURE TYPE

6EW6**GENERAL DATA****Electrical:**

Heater, for Unipotential Cathode:

Voltage (AC or DC) $6.3 \pm 10\%$ volts

Current 0.4 amp

Direct Interelectrode Capacitances:

	<i>Without External Shield</i>	<i>With External Shield^o</i>	
Grid No.1 to plate	0.04 max.	0.03 max.	μf
Grid No.1 to cathode, grid No.3 & internal shield, grid No.2, and heater.	10	10	μf
Plate to cathode, grid No.3 & internal shield, grid No.2, and heater	2.4	3.4	μf


Characteristics, Class A₁ Amplifier:

Plate Supply Voltage.	125	volts
Grid No.3	<i>Connected to cathode at socket</i>	
Grid-No.2 Supply Voltage.	125	volts
Cathode Resistor.	56	ohms
Plate Resistance (Approx.)	0.2	megohm
Transconductance.	14000	μmhos
Plate Current	11	ma
Grid-No.2 Current	3.2	ma
Grid-No.1 Voltage (Approx.) for plate $\mu\text{a} = 20$	-3.5	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-1/8"
Maximum Seated Length	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip) . .	1-1/2" $\pm 3/32$ "
Diameter.	0.650" to 0.750"
Dimensional Outline	<i>See General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No.E7-1)
Basing Designation for BOTTOM VIEW.	7CM

Pin 1-Grid No.1
Pin 2-Cathode
Pin 3-Heater
Pin 4-Heater
Pin 5-Plate



Pin 6-Grid No.2
Pin 7-Grid No.3,
Internal
Shield

6EW6



6EW6

SHARP-CUTOFF PENTODE

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE. 330 max. volts
GRID-No.3 (SUPPRESSOR-GRID) VOLTAGE. 0 max. volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE 330 max. volts
GRID-No.2 VOLTAGE. See Grid-No.2 Input

Rating Chart at front of Receiving Tube Section

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Positive-bias value. 0 max. volts

GRID-No.2 INPUT:

For grid-No.2 voltages up

to 165 volts 0.65 max. watt

For grid-No.2 voltages be-

tween 165 and 330 volts. See Grid-No.2 Input

Rating Chart at front of Receiving Tube Section

PLATE DISSIPATION. 3.1 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode 200 max. volts

Heater positive with respect to cathode 200[▲]max. volts

[○] With external shield JEDEC No.316 connected to cathode.


[▲] The dc component must not exceed 100 volts.



6EW6

AVERAGE CHARACTERISTICS

6EW6



ELECTRON TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY


92CM-9965

6EW6



6EW6

AVERAGE CHARACTERISTICS



ELECTRON TUBE DIVISION
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-9962